



VM-24HDCP

2x1:4 DVI (HDCP) Distribution Amplifier



The VM-24HDCP is a high-performance distribution amplifier for DVI signals. The unit reclocks and equalizes one of two input signals and distributes it to four identical outputs.

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support - HDMI Compressed Audio Channels.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI systems.
- Control - Front panel & IR switching.
- Worldwide Power Supply - 100–240V AC.
- Standard 19" Rack Mount Size - 1U. Rack "ears" included.



VM-24HDCP

TECHNICAL SPECIFICATIONS

INPUTS:	2 DVI, 1.2Vpp on a DVI Molex 24-pin (F) connector; DDC signal 5Vpp (TTL).
OUTPUTS:	4 DVI, 1.2Vpp on DVI Molex 24-pin (F) connectors; DDC signal 5Vpp (TTL).
MAX. DATA RATE:	6.75Gbps (2.25Gbps per graphic channel).
CONTROLS:	EDID SELECT, EDID READ, IN 1, IN 2 buttons, RS-232, IR.
INDICATOR LEDs:	OUTPUT STATUS LEDs.
POWER CONSUMPTION:	100-240V AC, 50/60Hz 17VA.
DIMENSIONS:	19" x 7" x 1U W, D, H, rack mountable.
WEIGHT:	2.5kg (5.5lbs) approx.
INCLUDED ACCESSORIES:	Power cord, rack "ears", null-modem adapter, Windows®-based control software, infrared remote control transmitter.

